

Cantesco® Aluma Galv and Cantesco® Zinc Galv

Short description

Cantesco® Aluma Galv formulated as an brilliant bright Zinc Spray containing a certain percentage of aluminium particles.

Cantesco® Zinc Galv is a highly concentrated grey Zinc Spray.

Both systems are available in a certified 500 ml aerosol can which allows long and sufficient periods of usage.

The product labelling will be according to customer designs and conferring to the dangerous goods regulations.

Application area

Cantesco® Aluma Galv with its aluminium particles re-constructs the brilliance of a galvanizing and ensures a reliable corrosion protection.

Cantesco® Zinc Galv is a high standard protection of weld seams and drill holes against corrosion. The reliable formula containing pure zinc particles provides a cathodic long-term rust-protection on point-, arc- and oxyacetylene welding.

Even with slight damages to the metal it provides a flexible protection.

Colour

- Cantesco® Aluma Galv - brilliant bright silver
- Cantesco® Zinc Galv - silver grey

Product features

- long-time corrosion protection / surface finish
- 24 months storage ability

Package size

500 ml aerosol can

Material consumption

Depends on consumer

Drying

Dust-dry after approx. 15 minutes.

Mixing ratio

ready to use

Ignition temperature

365°C

Explosion limits

Lower: 1,5 Vol%; Upper: 10,9 Vol%

Disposal

Must not be disposed together with ordinary household refuse.

Do not allow product to reach sewage system.

Substrate

Welds, galvanized steel, base iron and other ferrous surfaces

Application temperature

- Material, atmospheric and surface temperature: at least + 5°C to max. +30°C.
- Relative humidity: < 80 %
- The substrate temperature must be at least 3 K above dew-point temperature.

Application information

- The surface must be clean, dry and degreased before applying the spray.
- Shake the can well before use.
- The active substance needs to be applied cross-wise until the recommended thickness is reached.

Important notice

Hazard notes, protective measures, hazardous material classes and disposal can be found in the safety data sheet of this product. All products are provided in certified containers and labelled according to customer specifications in line with relevant hazardous substances and goods guidelines.

Protect from sunlight and temperatures exceeding 50°C, may burst if heated. Formation of explosive vapor/air mixtures. Can be stored in closed original containers in a dry place up to 24 months at a temperature between +10°C and +30°C. Frost should be avoided. To achieve the best results, it is recommended to store the material at room temperature for approx. 24 hours prior to use.

Based on our experience and to the best of our knowledge, this technical data is up to date and all information is current. As there might be operating conditions of which we have no knowledge and cannot have any knowledge, this data sheet shall be considered for information only and without responsibility. For the benefit of technical advances and the outcome of such advances, we reserve the right to make changes to the data without any prior notification. With the issuance of this publication, all prior technical information shall be considered null and void. When you contact us, you have the option to take advantage of our technical service consultants to find out about the various applications. Please ensure to request a written confirmation after receiving a verbal statement. For the rest, our terms and payment conditions apply.

Issue Coesfeld 2015-02-24